

AMENDMENTS TO THE CLAIMS

Sub
C1
1 (currently amended) A color correction method comprising:

obtaining reference outputs from an image sensor using a color image array, said reference outputs being indicative of outputs for a plurality of known reference colors, said plurality of known reference colors including at least three primary colors, and at least two other non-primary colors;

By
Cant
determining an error measure for ~~some~~ each of said plurality of known reference colors, said error measure representing a difference between said reference outputs and what would be expected for each of said reference outputs;

applying ~~determining~~ a weight factor to each said error measure for each ~~weighted error measure for at least one other~~ of said plurality of known reference colors ~~between said reference outputs and what would be expected for each of said reference outputs~~ to obtain a respective weighted error measure for each of said plurality of reference colors;

obtaining a color correction matrix which is adjusted to minimize said ~~error measure or~~ respective weighted error measure for each of said plurality of reference colors; and

using said color correction matrix to ~~simultaneously~~ simultaneously optimize color correction simultaneously for each of said plurality of reference colors to obtain a color-corrected image.

2. (canceled)

3. (currently amended) A method as in claim 1 wherein said color correction method comprises obtaining, for each of the plurality of reference colors,

$$(G_n' [\text{what expect to see}] - G_c [\text{actual}])^2 \cdot W_i = G_E$$

$$(R_n' - R_c)^2 \cdot W_i = R_E$$

$$(B_n' - B_c)^2 \cdot W_i = B_E$$

where G_n' , R_n' and B_n' are expected color values, G_c , R_c and B_c are actual color values, and W_i is a weighting factor for each of colors i , i varying from 1-j colors, and minimizing G_E , R_E , and B_E for each of the plurality of colors.

4. (previously presented) A method as in claim 3 wherein there are at least seven reference colors.

5. (previously presented) A method as in claim 3 wherein there are twenty-four reference colors.

6. (currently amended) An image sensor apparatus, comprising:
 an image sensor device, operating using a color filter array which provides color filtering such that colors transmitted to each pixel are measured to determine all color components that actually impinge on an area of said pixel; and
 an image processor, operating according to a color correction matrix adjusted to minimize respective weighted error measures, each said error measure representing a difference between a reference output for a known reference color from a color image array and what would be expected for said reference output, said color correction matrix being adjusted according to at least three primary colors, and at least two additional non-primary colors wherein said color correction matrix has an error measure for some colors weighted for color correction more than an error measure for other colors.

7. (previously presented) An apparatus as in claim 6 wherein said color correction matrix is adjusted according to at least three primary colors, white, and at least three colors other than said three primary colors and white.

8. (previously presented) An apparatus as in claim 6 wherein said color correction matrix is adjusted based on a total of twenty-four colors.

9. (previously presented) An apparatus as in claim 6 wherein said color correction matrix operates according to

$$(G_n' [\text{what expect to see}] - G_c [\text{actual}])^2 \cdot W_i = G_E$$

$$(R_n' - R_c)^2 \cdot W_i = R_E$$

$$(B_n' - B_c)^2 \cdot W_i = B_E$$

where G_n' , R_n' and B_n' are expected color values, G_c , R_c and B_c are actual color values, and W_i is a weighting factor for each of colors i , i varying from 1-j colors, and G_E , R_E , and B_E are minimized for each of the plurality of colors.

10. (canceled)

11. (previously presented) An apparatus as in claim 10 wherein red, green, and blue are weighted higher than other colors.

12. (previously presented) An apparatus as in claim 6 wherein said color correction matrix is adjusted according to all colors of a chromaticity chart.

13. (currently amended) A method of correcting an image from an image sensor, comprising:

dividing the image sensor into a plurality of pixels;

placing color separators over said plurality of pixels, such that each pixel receives incoming light that is filtered to emphasize one color component; and

obtaining a color correction matrix for said pixels, said color correction matrix being one which takes into account correction of incoming radiation for at least three primary colors, and two other non-primary colors, wherein respective error measures for said non-primary colors are weighted such that said correction matrix corrects for some of said non-primary colors more than said primary colors, each error measure representing a difference between a reference output for a known reference color from a color image array and what would be expected for each of said reference outputs.

Application No.: 09/209,982

Docket No.: M4065.0858/P858

14. (canceled)

*BT
cancel*